

CLOVER TFT DISPLAY



Clover’s TFT displays are designed to provide solutions to upgrade from standard monochrome displays. Our TFT displays’ range is from 3.5” to 10” which are suitable for industrial instruments, medical equipment, automation and GPS, etc. What’s more, We also provide controller board for customers to easily convert the RGB interface to MCU interface. The Mono TFT displays are with high contrast, brilliant brightness, wide viewing angle and fast response time.



STANDARD TFT LCD LIST

Model No.	Size	Resolution	Module Size L x W x H (mm)	Active Area L x W (mm)	Interface	Contrast	Brightness cd/m ²	Control Board
Color TFT								
CT35C3224A	3.5"	320 x 240	76.9 x 63.9 x 3.26	70.08 x 52.56	RGB	400:1	250	✓
CT43C4827A	4.3"	480 x 272	105.5 x 67.2 x 2.9	95.04 x 53.856	RGB	500:1	500	✓
CT50C8048A	5"	800 x 480	120.7 x 76.3 x 3.1	108.0 x 64.8	RGB	500:1	350	✓
CT70C8048A	7"	800 x 480	164.9 x 100.0 x 5.7	154.08 x 85.92	RGB	500:1	400	✓
CT70C1060A	7"	1024 x 600	165.75 x 105.39 x 4.8	153.6 x 90.0	LVDS	700:1	500	
CT10C1208A	10"	1280 x 800	229.46 x 149.1 x 3.4	216.96 x 135.6	LVDS	700:1	250	
Mono TFT								
CT35M2432A*	3.5"	240 x 320	62.90 x 86.54 x 4.1	53.28 x 71.04	MCU	TBD	TBD	
CT57M3224A	5.7"	320 x 240	159.5 x 108.4 x 6.4	115.2 x 86.4	MCU	800:1	1200	
CT62M6432A	6.2"	640 x 320	170.3 x 88.3 x 4.7	140.0 x 70.0	MCU	1000:1	1200	

* Under Development

If you have interest in our TFT displays & controller board, please do not hesitate to contact us for more information.

Any inquires or feedbacks from you will be highly appreciated. We assure you satisfying service and look forward to hearing from you in near future.

Email: cdl@cloverdisplay.com

Website: <http://www.cloverdisplay.com/>

Phone: (852) 2341 3238

Fax: (852) 2357 4237

If you no longer wish to receive these emails, please reply to this message with "Unsubscribe" in the subject line or simply click [unsubscribe](#)