



**CLOVER DISPLAY LTD.**

## LCD MODULE SPECIFICATION

**Model: CV9162E - \_ \_ - \_ \_ - \_ \_ - \_ \_**

Revision	10
Engineering	Timmy Kwan
Date	11 August 2010
Our Reference	9016

ADDRESS : 1<sup>st</sup> FLOOR, EFFICIENCY HOUSE, 35 TAI YAU STREET, SAN PO KONG,  
KOWLOON, HONG KONG.

TEL : (852) 2341 3238 (SALES OFFICE) (852) 2342 8228 (GENERAL OFFICE)

FAX : (852) 2357 4237 (SALES OFFICE)

E-MAIL : [cdl@cloverdisplay.com](mailto:cdl@cloverdisplay.com)

URL : <http://www.cloverdisplay.com>

**MODE OF DISPLAY**

**Display mode**

- TN positive
- TN negative
- STN :  Yellow green
- Grey
- Blue (negative)
- FSTN positive
- FSTN negative

**Display condition**

- Reflective type
- Transflective type
- Transmissive type
- Others

**Viewing direction**

- 6 O' clock
- 12 O' clock
- 3 O' clock
- 9 O' clock

**LCD MODULE NUMBER NOTATION:**

CV9162E- N N - S R - N 6 - T

|        | |        | |        | |        |

(1)        (2) (3) (4) (5) (6) (7) (8)

- \* (1)---Model number of standard LCD Modules
- \* (2)---Backlight type
  - N – No backlight
  - E – EL backlight
  - L – Side-lited LED backlight
  - M– Array LED backlight
  - C – CCFL
- \* (3)---Backlight color
  - N – No backlight
  - A – Amber
  - B – Blue
  - O– Orange
  - W–White
  - Y – Yellow green
- \* (4)---Display mode
  - T – TN
  - V – TN (Negative)
  - S – STN Yellow green
  - G – STN Grey
  - B – STN Blue (Negative)
  - F – FSTN
  - N – FSTN (Negative)
- \* (5)---Rear polarizer type
  - R – Reflective
  - F – Transflective
  - T – Transmissive
- \* (6)---Temperature range
  - N – Normal
  - W– Extended
- \* (7)---Viewing direction
  - 6 – 6 O'clock
  - 2 – 12 O'clock
  - 3 – 3 O'clock
  - 9 – 9 O'clock
- \* (8)---Special code for other requirements  
(Can be omitted if not used)

**GENERAL DESCRIPTION**

Display mode : 16 characters x 2 lines, COG LCD module

Interface : 4-bit parallel

Driving method : 1/16 duty, 1/5 bias

Controller IC : Novatek NT7603 or equivalent

For the detailed information, please refer to the IC specifications.

**MECHANICAL DIMENSIONS**


Item	Dimension	Unit	Item	Dimension	Unit
Outline Dimension			Character Size	2.24(L)x3.55(W)	mm
No Backlight (N)	48.2(L)x21.0(W)x2.9(H)	mm	Character Pitch	2.64(L)x3.95(W)	mm
LED Side Backlight (L)	48.2(L)x21.0(W)x6.8(H)	mm	Dot Size	0.4(L)x0.4(W)	mm
Viewing Area	43.9(L)x10.0(W)	mm	—	—	—

**CONNECTOR PIN ASSIGNMENT**

Pin No.	Symbol	Function	Pin No.	Symbol	Function
1	GND	Ground	7	DB4	Data bus line
2	VO	Input Voltage for LCD	8	DB5	
3	VDD	Supply Voltage for Logic	9	DB6	
4	RS	Register Select	10	DB7	
5	RW	Read / Write Select	11	A	Supply Voltage for backlight (+VE)*
6	E	Chip Enable	12	K	Supply Voltage for backlight (-VE)*


(\*) Note: Pin 11, 12 are for side-lited LED backlight revision only.

COUNTER DRAWING OF MODULE DIMENSION






White / Blue color side lited backlight 



TOLERANCE IF NOT SPECIFY SCALE ±0.5mm		SCALE N.T.S.	UNIT IN mm	CLOVER DISPLAY LTD. (HK)		SHEET 3 OF 5		
REV.	REVISION RECORD	DATE	CUSTOMER	APPROVED	MODEL NO.	CV9162E		
00	1st ISSUE	06 MAR 04	STANDARD	APPROVED	TITLE:	MODULE DIMENSION		
01	Add backlight dim. & spec	30 JUL 04			DRAWN BY:	LRJ	DATE:	06 AUG 10
02	Change white color backlight current	06 AUG 10			CHECKED BY:	<i>[Signature]</i>	DATE:	<i>[Signature]</i>
			CUSTOMER REF.	OUR REF.	X9016	APPROVED BY:	<i>[Signature]</i>	
						DATE:	<i>[Signature]</i>	

COUNTER DRAWING OF PIN OUT & BLOCK DIAGRAM

PIN NO.	SYMBOL	FUNCTION
1	GND	Ground
2	V5	Input voltage for LCD
3	VDD	Supply voltage for logic
4	RS	Register select
5	RW	Read / Write select
6	E	Chip enable
7	DB4	Data bus line
8	DB5	
9	DB6	
10	DB7	
*11	A	Supply voltage for backlight (+VE)
*12	K	Supply voltage for backlight (-VE)



Note(\*): Pin11,12 are used for side-lit backlight versions only.

TOLERANCE IF NOT SPECIFY ±0.5mm		SCALE N.T.S.	UNIT IN mm	CLOVER DISPLAY LTD. (HK)		SHEET 4 OF 5
REV.	REVISION RECORD		DATE	APPROVED	MODEL NO. CV9162E	
00	1st ISSUE		06 MAR 04		TITLE: PIN OUT & BLOCK DIAGRAM	
01	Add backlight dim. & spec		30 JUL 04		DRAWN BY: LRJ	DATE: 06 AUG 10
02	Change white color backlight current		06 AUG 10	APPROVED	CHECKED BY: <i>[Signature]</i>	DATE: <i>07 August</i>
					APPROVED BY: <i>[Signature]</i>	DATE: <i>9/6/10</i>
				OUR REF. X9016		
				CUSTOMER REF.		

**ELECTRICAL CHARACTERISTICS**

Conditions: VSS=0V, @Ta=25°C

Item	Symbol	MIN.	TYP.	MAX.	Unit
Supply Voltage	VDD	4.75	5.00	5.25	V
Supply Current	IDD	—	1.1	1.6	mA
Input Voltage for LCD (*)	VO	0.3	0.5	0.7	V
“H”Level Input Voltage	VIH	2.2	—	VDD	V
“L”Level Input Voltage	VIL	0.0	—	0.6	V

**Note (\*): There is tolerance in optimum LCD driving voltage during production and it will be within the specified range.**

## Side Backlight

Constant voltage driving:

Item	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Blue Backlight current	IBL	16	18	20	mA	VBL =3.5V
White Backlight current	IBL	12	14	16	mA	VBL =3.5V

Constant current driving:

Item	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Yellow Green Backlight voltage	VBL	—	2.0	2.4	V	IBL = 60 mA

**ABSOLUTE MAXIMUM RATINGS**

Please make sure not to exceed the following maximum rating values under the worst application conditions

Item	Symbol	Rating (for normal temperature)	Rating (for wide temperature)	Unit
Supply Voltage	VDD	7	7	V
Input Voltage	VT	-0.3 to VDD +0.3	-0.3 to VDD +0.3	V
Operating Temperature	Topr	0 to 50	-20 to 70	°C
Storage Temperature	Tstg	-10 to 60	-30 to 80	°C





**ELECTRO-OPTICAL CHARACTERISTICS**

MEASURING CONDITION: POWER SUPPLY =  $V_{OP} / 64 \text{ Hz}$   
 TEMPERATURE =  $23 \pm 5 \text{ }^\circ\text{C}$   
 RELATIVE HUMIDITY =  $60 \pm 20 \%$

ITEM	SYMBOL	UNIT	TYP. STN
RESPONSE TIME	$T_{on}$	ms	150
	$T_{off}$	ms	190
CONTRAST RATIO	$Cr$	-	15
	$V_{3:00}$	$^\circ$	45
VIEWING ANGLE	$V_{6:00}$	$^\circ$	70
	(6 O'clock) $V_{9:00}$	$^\circ$	45
	$Cr \geq 2$ $V_{12:00}$	$^\circ$	60

THE ELECTRO-OPTICAL CHARACTERISTICS ARE MEASURED VALUE BUT NOT GUARANTEED ONES.

**RELIABILITY OF LCD MODULE**

ITEM	TEST CONDITION FOR NORMAL TEMPERATURE	TEST CONDITION FOR WIDE TEMPERATURE	TIME
High temperature operating	50°C	70°C	240 hours
Low temperature operating	0°C	-20°C	240 hours
High temperature storage	60°C	80°C	240 hours
Low temperature storage	-10°C	-30°C	240 hours
Temperature-humidity storage	40°C 90% R.H.	60°C 90% R.H.	96 hours
Temperature cycling	-10°C to 60°C 30 Min Dwell	-30°C to 80°C 30 Min Dwell	5 cycle
Vibration Test at LCM Level	Freq 10-55 Hz Sweep rate: 10-55-10 at 1 min Sweep mode Linear Displacement: 2 mm p-p 1 Hour each for X, Y, Z	Freq 10-55 Hz Sweep rate: 10-55-10 at 1 min Sweep mode Linear Displacement: 2 mm p-p 1 Hour each for X, Y, Z	—

**SAMPLING METHOD**

SAMPLING PLAN: MIL-STD 105E  
 CLASS OF AQL: LEVEL II/ SINGLE SAMPLING  
 MAJOR-0.65% MINOR – 1.5%

**QUALITY STANDARD**

DEFECT	CRITERIA	TYPE	FIGURE
SHORT CIRCUIT	-	MAJOR	-
MISSING SEGMENT	-	MAJOR	-
UNEVEN / POOR CONTRAST	-	MAJOR	-
CROSS TALK	-	MAJOR	-
PIN HOLE	$MAX(a,b) \leq 1/4 W$	MINOR	1
EXCESS SEGMENT	$MAX(c,d) \leq 1/4 T$	MINOR	1
BUBBLES	$d^* \geq 0.2$ QTY=0	MINOR	2
BLACKS SPOTS	$d \leq 0.3$ N.A.** $0.3 < d \leq 0.4$ QTY $\leq$ 1 $0.4 < d$ QTY=0	MINOR	2
LINE SCRATCHES	$x \geq 0.7$ $y \geq 0.05$ QTY=0	MINOR	3
BLACK LINE	$x \geq 0.7$ $y \geq 0.05$ QTY=0	MINOR	3

\*d = MAX (d<sub>1</sub>,d<sub>2</sub>)

\*\* N. A . = NOT APPLICABLE

DEFECT TABLE : B






fig . 1



POLARIZER BUBBLES / SPOTS

fig . 2



LINE SCRATCHES / BLACK LINE

fig . 3

QUALITY STANDARD ( CONT . )

DEFECT		CRITERIA	TYPE	FIGURE
	CONTACT EDGE	$e \leq 1/2T$ $f \leq 1/3W$ $g \leq 3.5$		4
CHIPS	BOTTOM GLASS	$p \leq 1.0$ $q \leq 3.5$ $r \leq 1/2T$	MINOR	4
	CORNER	$a \leq 1.5$ $b \leq W$		4
	TOP GLASS	$a \leq 3.0$ $b \leq 1/3T$ $c \leq 1/2W$		5
GLASS PROTRUSION		$a \leq 1/4 W$	MINOR	6
RAINBOW		-	MINOR	-

UNLESS STATE OTHERWISE , ALL UNIT ARE IN MILLIMETER .

DEFECT TABLE : B




fig . 4




fig . 5





fig . 6



## HANDLING PRECAUTIONS

### (1) CAUTION OF LCD HANDLING & CLEANING

The polarizing plate on the surface of the panel is made from organic substances. Be very careful for chemicals not to touch the plate or it leads the polarizing plate to deteriorate.

If the use of a chemical is unavoidable, wipe the panel lightly with soft materials, such as gauze and absorbent cotton, soaked in a solvent.

\*Usable solvent: Alcohol (ethanol, IPA and the like)

\*Appropriate solvent: Ketones, ethyl alcohol

Avoid wiping with a dry cloth, since it could damage the surface of the polarizing plate and others.

Do not expose to direct sunlight or fluorescent light for a long time

### (2) CAUTION AGAINST STATIC CHARGE

The LCD modules use CMOS LSI drivers, so customers are recommended that any unused input terminal would be connected to  $V_{DD}$  or  $V_{SS}$ , do not input any signals before power is turned on, and ground your body, work/assembly areas, assembly equipment to protect against static electricity.

### (3) ESD PRECAUTION

Inputs and outputs are protected against electrostatic discharge in normal handling. However, to be totally safe, it is recommended to take normal precautions appropriate to handling LCM module. For example: product surface grounding.

Always take ESD precaution when handling the *LCD Module*. Components are exposed for direct finger touches and can be damaged unless ESD precaution is taken.

### (4) PACKAGING

Avoid intense shock and falls from a height and do not operate or store them exposed to direct sunshine or high temperature/humidity for long periods.

### (5) CAUTION FOR OPERATION

The viewing angle can be adjusted by varying the LCD driving voltage  $V_O$ .

Driving voltage should be kept within specified range, excess voltage shortens display life.

Response time increases with decrease in temperature.

Display may turn black or dark Blue at temperature above its operational range; this is however not destructive and the display will return to normal once the temperature falls back to range.

Mechanical disturbance during operation (such as pressing on the viewing area) may cause the segments to appear "fractured". They will recover once the display is turned off.

Condensation at terminals will cause malfunction and possible electrochemical reaction. Relative humidity of the environment should therefore be kept below 60%.

### (6) SAFETY

Liquid crystal may leak out of a damaged LCD, it is recommended to wash off the liquid crystal by using solvents such as acetone or ethanol and should be burned up later.

If any liquid leak out of a damaged glass cell comes in contact with your hands, wash it off with soap and water immediately.

## WARRANTY

CLOVER will replace or repair any of her LCD module in accordance with her LCD specification for a period of one year from date of shipment. The warranty liability of Clover is limited to repair and/or replacement. Clover will not be responsible for any subsequent or consequential event.